

ventilation system will help prevent attic heat build-up; attic moisture and condensation; weather infiltrations (e.g.) drifting snow, wind-driven rain; and prevents ice dam build-up. Research has shown that proper ventilation is required if the shingles are to last their design life.

CODE REQUIREMENTS

Asphalt shingles, roof slopes 4/12 and greater. A typical installation of asphalt shingles is shown in the illustration for use on roofs 4/12 and greater. However, the code also permits application on a roof that has a slope of less than 4/12 if the low slope roofing procedures are used.

Fasteners: Fasteners for asphalt shingles shall be galvanized steel, stainless steel, aluminum or copper roofing nails, minimum 12 gage shank with a minimum 3/8" diameter head, ASTM F 1667, of a length to penetrate through the roofing materials and a minimum of 3/4" into the roof sheathing. Where the roof sheathing is less than 3/4" thick, the fasteners shall penetrate through the sheathing. Fasteners shall comply with ASTM F 1667.

Underlayment: The code requires that underlayment of one layer of non-perforated Type 15 felt lapped 2" horizontally and 4" vertically to shed water. In addition, and ice barrier that consists of at least two layers of underlayment cemented together or of a self-adhering polymer modified bitumen sheet, shall be used in lieu of normal underlayment and extend from the eave's edge to point at least 24" inside the exterior wall line of the building.

Valleys: Valley linings shall be installed in accordance with manufacturer's installation instructions before applying shingles. Valley linings of the following types shall be permitted.

1. For open valley (valley lining exposed) lined with metal, the valley lining shall be at least 24" wide and of the corrosion-resistance metals in Table R905.2.8.2.
2. For roof slopes from two units vertical in 12 units horizontal (17% slope), up to four units vertical in 12 units horizontal (33% slope), underlayment shall be two layers applied in the following manner. Apply a 19" strip of underlayment felt parallel with and starting at the eaves, fastened sufficiently to hold in place. Starting at the eave, apply 36" wide sheets of underlayment, overlapping successive sheets 19", and fastened sufficiently to hold in place. For


roof slopes of four units vertical in 12 units horizontal (33% slope) or greater, underlayment shall be one layer applied in the following manner. Underlayment shall be applied shingle fashion. Parallel to and starting from the eave and lapped 2", fastened sufficiently to hold in place. End laps shall be offset by 6'.

3. For closed valleys (valley covered with shingles), valley lining of one ply of smooth roil roofing complying with ASTM D 224 Type II or Type III and at least 36" wide or valley lining as described in items 1 and 2 above shall be permitted. Specialty underlayment complying with ASTM D 1970 may be used in lieu of the lining material.

Cricket and saddles. A cricket or saddle shall be installed on the ridge side of any chimney greater than 30" wide. Cricket or saddle coverings shall be sheet metal or the same material as the roof covering.

Sidewall flashing. Flashing against a vertical sidewall shall be by the step-flashing method.

Other flashing. Flashing against a vertical frost wall, as well as soil stack, vent pipe and chimney flashing, shall be applied according to asphalt shingle manufacturer's printed instructions.



Construction Codes and Licensing Division
Building Codes and Standards
 443 Lafayette Road No.
 St. Paul, MN 55155-4341
 651-284-5068
 Fax 651-2845749
www.doli.state.mn.us



ASPHALT SHINGLE ROOFS PERMITS MADE EASY

Guidelines for planning Asphalt shingle roofing



City of Anoka
 2015 First Avenue North
 Anoka, MN 55303

Tel: 763-576-2720
 Fax: 763-576-2727
www.ci.anoka.mn.us

CONSIDERATIONS

Before undertaking any re-roofing project there are several questions that should be considered to insure a successful project and make it go smoothly. You should also familiarize yourself with all aspects of the re-roofing process before you begin. The fact is, there are various conditions about your roof that may limit your production choices or affect the cost of your roofing job.

Do I need a new roof?

How old is it? A roof that has been properly installed, ventilated and has not been damaged can last 20 years or more. An inspection of the roof should be done periodically. Look for cracks, curled or cupped shingles, worn mineral coatings, exposed nails, previous patches, holes, and exposed underlayment or sheathing.

Does the roof leak? If the answer is yes it is necessary to determine why. If you have inspected the roof and it looks sound, your problem could be roof flashing. Many roof leaks are the result of bad or misapplied flashings. You should spend time in the attic looking for water stains, particularly around vents chimneys, and vertical wall elements above the roof. A garden hose can help you find the leak. Flashing can sometimes be replaced or repaired without installing a whole new roof.

Do it myself or hire a professional? This is a questions that only you can answer based on your skill level and time. An asphalt roofing project can be successfully accomplished by the homeowner if you take the time to become familiar with the roofing procedures. Be sure to plan your project around the weather and allow enough time to get a proper cover on the roof before it rains. Steep sloped asphalt roofs and those with multiple valleys can present special problems, so be sure you have the right equipment and skills before undertaking this type of roofing project. Other types of roofs such as wood shingles, shakes, and clay tile are not normally taken on by the 'do-it-yourself' homeowner because of the special skills required. Remember, if you decide to hire a professional be sure the company is a state licensed contractor or roofer.

Should I overlay the existing roof or tear off the existing shingles? New roof coverings shall not be installed without first removing existing roof coverings (International Residential Code Section 907) There are advantages to tearing off the old roof before installing a new roof, in addition to it being required

by the code. For example:

- If there are any defects in the roof deck, they will be revealed when the roof is torn off. These defects should be repaired before applying the new roof.
- If condensation problems exist in the attic, they too will be revealed when the roof is torn off. Properly designed attic ventilation can then be installed in order to help eliminate such problems.
- When the old roof is torn off, an ice-protection underlayment must be installed before applying the new roof. This will help prevent against ice damage.
- Tearing off the old roof and starting with a clean deck before re-roofing may result in a smoother finished roof system.

Tearing off the old roof will typically result in a longer roof life than when the roof has been laid over. This is because they are installed smooth over sound material and have new under layment installed.

What is roof slope and does it limit the choice of shingles? R905.2.2 Slope. (2000 International Residential Code) Asphalt shingles shall only be used on roof slopes of 2 units vertical in 12 units horizontal (2:12) or greater. For roof slopes from 2 units vertical in 12 units horizontal (2:12) up to 4 units vertical in 12 horizontal (4:12).


The slope of the roof is measured by the vertical rise of the roof to the horizontal run and is expressed as a fraction. A 4/12 roof slope means the roof rises 4 feet for ever 12 feet of horizontal. Roof slopes do limit the choice of shingles that can be used. For example: A roof slope below 2/12 may allow ice and water to back up under the shingles.

Roof slopes between 2/13 and 4/12 can use shingles, but require roof application techniques to take into account a greater potential for Ice dam water backup. Slopes of 4/12 and above can use standard asphalt roofing applications.

Always refer to the manufacturer's application instructions.

ROOF VENTILATION

Ventilation is required. Enclosed attics and enclosed rafter spaces formed where ceilings are applied directly to the underside of the roof rafters shall have cross ventilation for each separate space by ventilating openings protected against the entrance of rain or snow. Ventilating openings shall be provided with corrosion-resistant wire mesh. With 1/8"



minimum to 1/4" maximum openings.

Minimum area. The total net free ventilating area shall not be less than 1 of 150 of the area of the space ventilated exempt that the total area is permitted to be reduced to 1 to 300, provided at least 50% and not more than 80% of the required ventilating area is provided by ventilators located in the upper portion of the space to be ventilated at least 3 feet above eave or cornice vents. As an alternative, the net free cross-ventilation area may be reduced to 1 to 300 when a vapor barrier having a transmission rate not exceeding 1 perm (57.4 mg/s-m²Pa) is installed on the warm side of the ceiling.

Even if you feel you have had satisfactory ventilation performance with your old roof, it might be necessary to add ventilation with your new roof to meet these standards.

What function does shingle underlayment serve? An underlayment, commonly know as roofing felt, will:

- Protect the roof deck from moisture prior to shingle application.
- Provide a degree of back-up protection in the event water gets under roofing shingles.

Protection against ice dams can be obtained by using a special waterproof shingle underlayment at the eaves or lower edges of the roof, in addition to installing adequate ventilation and proper insulation in the attic. The code in Minnesota requires this special waterproof shingle underlayment at the eaves or lower edges of the roof.

How can you determine if the roof is properly ventilated? A roof needs to breath. An effective